

Plug n Clear



YEARS OF WARRANTY

3

STANDARD

8000 HOURS

Cell

As defined by EN 17645.
Go to report pages to see
the complete detail by item.

DIY SALT CHLORINATOR: CONNECT, TOUCH, RELAX

- **DIY salt chlorinator:** your swimming pool is disinfected and disinfectant
- Very easy installation (no gluing of the cell required) for a **"plug and play"** solution
- **Intuitive use, the salt chlorinator comes pre-programmed!**
- **Salt chlorinator compatible** with in-ground pools, above-ground pools and spas
- **Large and clearly arranged** user interface
- **Compact and attractive design**, suitable for small technical facilities
- Three tactile control buttons
- **Three operating modes possible** (including a temperature-dependant mode)



INCLUDED



Chlorine production



Plug & play



Do It Yourself



Temperature reading

ELECTRONIC BOX

Description	PNCLEAR-05	PNCLEAR-10	PNCLEAR-20
Maximum production Cl ₂ /h	5 g/h	10 g/h	20 g/h
Salt concentration	3 to 100 g/L		
Language	Universal		
Estimated pool volume	20 m ³	40 m ³	80 m ³
User interface	2 x 11 segments + 3 tactile buttons		
Power supply	110 - 230 VAC; 50/60 Hz		
Waterproofing standard	IPX3		
Dimensions	222 x 174 x 71 mm		
Material	Fireproof ABS		
Consumption	45 W	85 W	160 W
Output	3 A 14 V	5.5 A 15 V	6.5 A 23 V
Mode	3 programmes: Manuel, Boost, Smart		
Temperature sensor	Included		
Safety	Mechanical flow sensor + cell auto-detection		
Alarms	Flow, low production, temperature < 10 °C		
Maximum operating temperature	45 °C		

CELL

Titanium plate	4 titanium plates	7 titanium plates	11 titanium plates
Minimum flow rate	5 m ³ /h		
Titanium plate dimensions	120 x 50 mm		
Support material	Transparent PVC		
Cell connection diameter	50 mm		
Cell position	Horizontal		
Cell mounting	Screwed onto Ø 50 mm pipe		
Cable length	2 m		
Maximum pressure	4 kg/cm ²		
Cell operating time	Counter included		
Self-cleaning	Programmable polarity reversal (6 hours by default)		
Maximum operating temperature	45 °C		

ACCESSORIES

1.5" connector pack (2 units)	GLX-DIY-CCN15
2" connectors pack (2 units)	GLX-DIY-CCN2
50 mm glued connector pack (2 units)	SP3200UNKIT50
63 mm glued connector pack (2 units)	SP3200UNKIT63