

Easy Chem



YEARS OF WARRANTY



As defined by EN 17645.
Go to report pages to see
the complete detail by item.

CONSISTENCY, DESIGN AND PERFORMANCE

- **A new design in concordance with all Water Treatment range!**
- **One full range of dosing systems** dedicated to disinfect your swimming pool up to 130m³.
- **Hayward® Santoprene tube** with unique design on the market
- **Large screen** for Easy Chem double
- **2 alarms** for Easy Chem single and **4 alarms programmable** for Easy Chem Double
- **Installation kit** included

INCLUDED



Easy Chem
Double Only

Programmable
alarm

Hayward®
Santoprene tube

AVAILABLE OPTIONS



Flow Switch



Empty tank detection



Ref.	EASY-CHEM-SPH	EASY-CHEM-SRXG	EASY-CHEM-SRXGS	EASY-CH-DPHRXG	EASY-CH-DPHRXGS
Product name	Easy Chem pH Single	Easy Chem ORP Single	Easy Chem ORP Pilot Single	Easy Chem pH + ORP Double	Easy Chem pH + ORP Pilot Double
Average Pool Volume	Indoor 5 – 130 m³ / Outdoor 5 – 110 m³				
Flow Rate	1.5 L/h				
Pressure	1.5 Bar				
Power Supply	230 Vac 50/60Hz		230 Vac 50/60Hz	230 Vac 50/60Hz	230 Vac 50/60Hz
Output Type	Peristaltic pump		Schuko 230Vac ORP	Peristaltic pump	pH peristaltic pump, Schuko 230Vac ORP
Liquid injection functioning	Proportional dosing		On/Off dosing	On-Off, Timed, Proportional dosing	
Power Switch On/Off	Yes				
Calibration	1 point			2 points (4 and 7), 1 point, by reference	
Measure Range	3.8-8.2 pH	400 – 999 mV		0-14 pH / 0-999 mV	
Measurement Accuracy	±0.1 pH	±10 mV		±0.02 pH; ±3 mV	
Operating T°	10-50 °C				
Screen	Digit 7 segment high visibility Led Display			Alphanumeric Display 2 lines 16 lecters	
Languages	None			5 (EN, FR, IT, ES, DE)	
Proctection Rating	IP55				
Connectivity	None				
Insulated measure	Yes by electronic				
Overdosing Alarm	Yes configurable (activated 120 min)				
Out Of Range Alarm	Yes following mesure range			Yes configurable (activated)	
Flow Switch connection	–			Yes configurable (not activated)	
Level chemical of product Alarm	–			Yes configurable (not activated)	
Circulation pump connection	–			Yes configurable (activated) (230V contact)	
Tube type	Hayward® Santoprene compatible with all acid concentration (sulfuric, chloridric and multi)				
Probe include	Plastic pH double junction	Plastic ORP Gold double junction		Plastic pH double junction Plastic ORP Gold double junction	
Temperature probe	–			Included	
Additional aux. relay	–			1 pH, 1 ORP, 1 alarm	
Dimensions (W x H x D)	111 x 185 x 110			196 x 234 x 102	
Weight	0.6 Kg		0.5 Kg	3.0 Kg	2.9 Kg
Recommendation	Change Hayward® Santoprene tube every season				

AVAILABLE OPTIONS

—	J-OPTION-FLOW AQR-PLUS-CANNE KV02
---	---