

# Lovibond® Water Testing Tintometer® Group



## Scuba3s

Smart electronic pool tester for advanced pool and spa control



- Wireless data transfer via NFC
- Lovibond® PoolAssistant app for pool maintenance & measurement results
- All important pool parameters
- Light signal (green/red) to indicate safe water conditions

Part Number: 216200

### NFC: Data transmission via chip

**The passive NFC chip** The passive NFC chip in the Scuba3s ensures wireless data transfer to an external device with an active NFC reader (e.g. smartphone). It works like putting on your debit card when shopping:

Simply hold the mobile phone close to the Scuba3s - and everything is on the device. All data records are transferred simultaneously and are immediately available in the PoolAssistant app for evaluation. A data set includes the serial number and firmware version of the device, the name and number of the method, the dates and time of the measurement, the results and the units. A cloud is also available for data storage.

### The PoolAssistant app: Quick overview always & everywhere

**The PoolAssistant app** helps you to evaluate the measurement results. After transfer via NFC, up to 3 users can immediately call up the data for each control parameter for a maximum of 5 pools. The app also classifies the results as diagrams for you and gives you tools for the right pool care, the appropriate chemistry and water quality. In the FAQ section, all important questions about pool water care, water hygiene or Langelier index are answered. You can also get valuable tips here.

### Light signals for instant certainty

**The light signals** in the Scuba3s immediately show via the coloured backlight of the display whether the measurement result "fits" or not. If the light is green, the measurement result is within the ideal measuring range and you can start having fun in the pool. If the light is red, caution is advised: The measurement result is above or below the globally accepted measurement range for safe swimming. Also when evaluating data with the PoolAssistant app, the results are classified

with green and red signal colours. The app also helps you to find the cause.

### More control parameters

**With 11 tests**, the Scuba3s offers even more possibilities to control the water quality in the pool based on the most important ingredients. For this purpose, choose with just a few button presses: chlorine (total, free, bound), bromine, pH value, alkalinity-m, calcium hardness, cyanuric acid, active oxygen, copper and phosphate provide information on whether the water quality in the pool is correct. The measuring process is now even faster.

### New design, more functionality

**Its ergonomic design** remains: The Scuba3s also fits comfortably in one hand. The back is flattened so that it cuts a good figure everywhere. With the screwable battery compartment, the electronic pool tester is guaranteed waterproof and joins in every pool fun with reliable results. With 4 multifunction buttons, you can easily find your way around the user menu on the larger display accompanied by intuitive animations and icons.

### Industry

Pool Domestic | Pool Services

### Application

Pool Water Control

## Scuba3s

The Scuba is a must-have at every pool worldwide. The new generation of the popular electronic pool tester now makes monitoring pool hygiene even faster, more versatile, more handy and easier. Mobile analysis management included!

### Measuring Range

Test Name	Measuring Range	Chemical Method
Alkalinity-m T	5 - 300 mg/L CaCO <sub>3</sub>	Acid / Indicator
Bromine T	0.2 - 13.5 mg/L Br <sub>2</sub>	DPD
Chlorine T	0.1 - 6.0 mg/L Cl <sub>2</sub> <sup>a)</sup>	DPD
Copper T	0.1 - 5 mg/L Cu <sup>a)</sup>	Biquinoline
CyA T	20 - 120 mg/L CyA	Melamine
Hardness Calcium (B) T	50 - 500 mg/L CaCO <sub>3</sub>	Murexide
Oxygen active T	0.2 - 10 mg/L O <sub>2</sub>	DPD
Phosphate LR T	0.06 - 3.0 mg/L PO <sub>4</sub>	Phosphomolybdenum Blue
pH-value T	6.5 - 8.4 pH	Phenol Red

### Technical Data

<b>Optics</b>	White LED, multichannel optical sensor with diffusor.
<b>Display</b>	LCD dot matrix with backlight (white/red/green), 35 x 25 mm
<b>Interfaces</b>	NFC (Near Field Communication)
<b>Operation</b>	Foil keypad
<b>Auto – OFF</b>	Yes
<b>Internal Storage</b>	100 data sets
<b>Power Supply</b>	2 batteries (AA)
<b>Battery Life Time</b>	approx. 5000 measurements (without backlight)
<b>Portability</b>	Portable
<b>Degree of Pollution</b>	2
<b>Maximum altitude above sea level</b>	3500 m
<b>Environmental Conditions</b>	temperature: 5-50 °C relative humidity: 30-95 %, non-condensing
<b>IP Rating</b>	IP 65
<b>Compliance</b>	CE UKCA
<b>Dimensions</b>	70 x 45 x 145 mm
<b>Weight</b>	165 g
<b>Weight with Packaging</b>	165 g

## Delivery Scope

- Scuba3s In plastic box
- 20 DPD No.1 tablet reagents
- 20 Phenol Red Photometer tablet reagents
- 10 DPD No.3 *Evo* tablet reagents
- 10 CyA-Test tablet reagents
- 10 Alka-M-Photometer tablet reagents
- 10 Calcio-H No.1 tablet reagents
- 10 Calcio-H No.2 tablet reagents
- Instruction manual
- 2 Batteries (AA)
- blue lid
- Stirring rod

### Title

### Part Number

Rubber seal cap for Scuba	19802218
Stirring rod, blue, 10 cm	364107

---

**Tintometer GmbH**

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Germany

**The Tintometer Limited**

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
sales@lovibond.uk  
www.lovibond.com  
UK

**Tintometer China**

9F, SOHO II C. No.9 Guanghualu,  
Chaoyang District,  
Beijing, 100020  
Customer Care Tel.: +86 (021) 69910081  
Tel.: +86 10 85251111 Ext. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

**Lovibond Tintometer Sdn Bhd**

Unit B-3-12, BBT One Boulevard,  
Lebuh Batu Nilam 2, Bdr Bkt Tinggi,  
41200, Klang, Selangor,  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

**Tintometer Brazil**

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brazil

**Tintometer Inc.**

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
USA

**Tintometer India Pvt. Ltd.**

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

**Tintometer Spain**

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain